

JS6-4.5



Applications

- › UPS/EPS
- › Power systems
- › Telecommunications system
- › Emergency lighting、Auto control system
- › Solar/wind generating storage cyclic
- › Other general purpose

Specification


Nominal Voltage	6V
Nominal Capacity	4.5Ah
Design life	5 years
Terminal	F187
Approx. Weight	Approx0.75kg (1.65lbs)
Container Material	ABS
Rated Capacity	4.50Ah 20Hour Rate (0.225A to 5.25V)
	3.51Ah 3Hour Rate (1.17A to 5.25V)
	2.97Ah 1Hour Rate (2.97A to 4.80V)
Internal resistance	Full charged at 25°C: 25.0 mΩ
Max. Discharge Current	67.5A(5S)
Operating Temperature	Discharge: -20 ~50°C(-4 ~ 122°F)
	Charge: -20 ~50°C(-4 ~ 122°F)
	Storage: -20 ~50°C(-4 ~ 122°F)
Charge current: Max.1.13A ; Recom.0.45A	
Charge Method (25 °C)	Float Charge:6.75-6.90V,recom.6.75V(-9mV/ °C)
	Equalize charge:6.90-7.05V,recom.7.05V(-12mV/ °C)
	Cycle charge:7.20-7.50V,recom.7.20V(-15mV/ °C)
Self discharge	3% of capacity declined per month at 25°C

General Features

- › High corrosion resistant performance: Pb-Ca multi-alloy grid
- › High energy density and power density
- › Optimized capability of instant high-current discharging
- › Excellent charge acceptance ability
- › Excellent deep cycle discharge capability
- › Strong high and low temperature performance
- › Precision sealing technology



Dimension: 71(L)×47(W)×97(H)×101(TH) Unit: mm



Constant Current Discharge Characteristics Unit: A (25°C, 77°F)


FV/Time	5min	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
1.60V	17.8	11.7	8.69	5.69	2.97	1.70	1.24	0.995	0.846	0.558	0.446	0.239
1.65V	17.7	11.2	7.97	5.40	2.79	1.63	1.21	0.963	0.828	0.549	0.441	0.234
1.70V	14.5	10.5	7.43	5.24	2.70	1.60	1.18	0.914	0.819	0.540	0.432	0.230
1.75V	13.5	10.0	6.93	5.12	2.61	1.56	1.17	0.900	0.783	0.527	0.423	0.225
1.80V	12.4	9.41	6.44	4.95	2.52	1.52	1.10	0.882	0.752	0.513	0.414	0.216

Constant Power Discharge Characteristics Unit: W/cell (25°C, 77°F)


FV/Time	5min	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
1.60V	33.5	21.0	15.9	9.62	5.45	3.19	2.35	1.88	1.60	1.05	0.863	0.473
1.65V	30.8	19.9	14.9	9.55	5.12	3.07	2.28	1.82	1.57	1.04	0.847	0.460
1.70V	28.2	19.3	14.3	9.52	4.97	3.01	2.24	1.73	1.52	1.03	0.840	0.456
1.75V	25.6	18.7	13.7	9.42	4.82	2.94	2.21	1.71	1.49	0.985	0.821	0.446
1.80V	23.0	18.1	13.1	9.35	4.76	2.92	2.15	1.70	1.46	0.952	0.804	0.443

JS6-4.5


Discharge characteristic




Charging characteristic




The effect of temperature on capacity




The effect of discharge depth on cycle life



Curves of self-discharge



The effect of temperature on float life



© www.kijo.com.cn ✉ info@kijo.com.cn

Jiangxi Jingjiu Power Science&Technology Co. Ltd.

Add: 1388 Fushan No.1 Street, Xiaolan Economic Development Zone, Nanchang City, Jiangxi Province, China.

☎ +86-791-85982779 ☎ +86-791-85989842

Jiangxi Jingjiu Power (Jiujiang) Co. Ltd.

Add: Xiwang Rd, Aicheng Industrial Park, Yongxiu Country, Jiujiang City, Jiangxi Province, China.

